

Drying Cabinets

LTE offers a wide selection of laboratory drying cabinets. From bench and wall-mounted versions to large floor-standing models. We also offer a range of energy efficient drying cabinets. With capacities from 100 to 1000 litres, there will be a model to suit your particular requirements.

FILTERED AIR DRYING CABINET

- The fine filter on this model reduces the amount of contamination entering the cabinet, thereby ensuring a cleaner environment for freshly washed items.
- The temperature is thermostatically controlled and the system is protected by an over-temperature cut-out device.

ECONOMY DRYING CABINET

- This range of large capacity cabinets provides efficient drying at an economical price.
- All models have heaters situated below a perforated base plate and are vented from the top. Fan extraction models draw the moist air upwards and direct it to the outside.
- Temperature control is by means of an energy regulator. Single or double toughened glass doors are provided, dependent on the model chosen.

SLIDING DOOR DRYING CABINET

For straightforward natural convection drying, this bench or wall-mounted range represents excellent value for money. There is a choice of stainless steel or epoxy coated finish.

ECO-DRYING CABINET

The Eco-DC range of energy efficient drying cabinets has been designed to reduce typical energy usage by up to 50% when compared to traditional drying cabinets. Insulation is provided to 5 sides of the cabinet, and temperature is electronically controlled and digitally displayed. Data sheets are available on request.

TECHNICAL AND ORDERING INFORMATION:

Drying Cabinet Type	Cat No:	Cap. Litres	Air Circulation	Max Temp. °C	Internal Dims. HxWxD (mm)	External Dims. HxWxD (mm)	Shelves/positions	Mass kg	Power Rating, (Watts)
Filtered Air	322/0105/00	534	Fan circulated	65	1115 x 785 x 610	1380 x 790 x 640	3/6	49	3000
Economy	322/0106/00	545	Natural convection	65	1480 x 625 x 590	1630 x 635 x 610	4/28	73	1500
	322/0108/00		Fan extracted						
Economy	322/0107/00	1000	Natural convection	65	1480 x 1150 x 590	1630 x 1160 x 610	4/28	124	2500
	322/0109/00		Fan extracted						
Sliding Door Epoxy Coated	322/0103/00	100	Natural convection	85	425 x 778 x 302	520 x 780 x 330	2/21	16	650
	322/0104/00	180			555 x 995 x 325	650 x 1000 x 350	2/35	27	1150
Sliding Door Stainless Steel	322/0101/00	100	Natural convection	85	425 x 778 x 302	520 x 780 x 330	2/21	16	650
	322/0102/00	180			555 x 995 x 325	650 x 1000 x 350	2/35	27	1150
Eco-DC	DC/LOW/100	100	Natural convection	85	425 x 778 x 302	630 x 870 x 375	2/21	25	650
	DC/LOW/180	180			555 x 995 x 325	760 x 1090 x 398	2/35	38	1150



Filtered Air Drying Cabinet



Economy Drying Cabinet - 545L



Economy Drying Cabinet - 1000L



Sliding Door Drying Cabinet



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

