| Specifications | |
|---|---|
| External Dimensions mm (Wx-DxH) | 650 x 600 x 1982 |
| Internal Dimensions mm (Wx-DxH) | 600 x 600 x 760 |
| Working Aperture mm (WxH) | 590 x 300 |
| Face Velocity | 0.5 m/sec |
| Airflow | 320 $m^3$/hr |
| Carbon Filter Type | Formalin |
| Filter Size mm | 600 x400 x 115 |
| Filter Weight | 14kg |
| Pre-Filter | Filtrete |
| Internal Lighting | 18 watt fluorescent |
| Fan | Centrifugal, Brushless & Sparkless |
| Water Supply | Optional |
| Foot Switch Control | Optional |
| Hand Operated Controls | Standard |
| Built-in 50 litre Formalin Tank | Optional |
| Noise Level | <57 db(A) |
| Electrical Supply | 2 x 240v - 400watts |
| Construction | Head: Epoxy Powder Coated Zintec Steel with 6mm clear acrylic front and side upper panels. |

# Circulaire 650FDS Compact Formalin Dispensing Station

The Circulaire 650FDS provides a compact and safe solution to the dispensing of Formalin in Operating Theatres, Pathology Laboratories & Mortuaries.

It is free standing and has a footprint of less than 0.4m2. It is extremely simple to use, just place your container of formalin into the base section, connect up and press the front mounted button (or optional foot switch) to dispense the formalin through the tap.

The upper cabinet provides full fume containment making sure that all formalin fumes are kept well away from the operator. The large capacity carbon filter ensures that no fumes are returned into the working area. This filter provides 3 to 4 years of life under normal use and is extremely easy to change when required. Where additional safety is required an outlet carbon filter can be fitted along with a filter saturation alarm to detect chemical breakthrough.

# Wolf Laboratories Limited

**www.wolflabs.co.uk**

Wolflabs

Tel: 01759 301142 Fax:01759 301143 sales@wolflabs.co.uk

## Use the above details to contact us if this literature doesn't answer all your questions.

## Pricing on any accessories shown can be found by keying the part number into the search box on our website.

**The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.**